



The **PRIMO** Collection great quality, great value

UPDATED CATALOGUE

ANGLO-EAST TRADING CO. (HK) LTD

ROOM 906, BLOCK B, PO LUNG CENTRE, 11 WANG CHIU ROAD,
KOWLOON BAY, KOWLOON, HONG KONG

英東貿易(香港)有限公司
香港九龍九龍灣宏照道11號寶隆中心B座906室

TEL: (852) 2375 1111 FAX: (852) 2375 3409
E-MAIL: SALES@ANGLO-EAST.HK

CONTACT US



MINIBAR SYSTEMS

smart bars • smart people • smart solutions

 A SWISS COMPANY



PRIMO - great quality, great value

PRIMO minibars have been quality engineered – with generous internal space, simple and stylish design, **low energy consumption** and **silent absorption technology**. Primo Range, a great value for your hotel.



PRIMO 30 glass door



PRIMO 40 solid door

Features

- Stocking capacity of up to 38 facings
- Adjustable transparent door racks for high visibility
- Removable shelving for easy cleaning
- Thermal insulation manufactured with cyclopentane
- Fully automatic defrost and easily adjustable thermostat
- Strong door hinges convertible left to right
- All-round magnetic seals to keep the door perfectly shut
- Integrated door handles
- Lock (can be deactivated)
- Option: Full glass door
- We meet all global compliances and are fully certified



PRIMO 42D drawer

Technical Specifications

	PRIMO 30	PRIMO 40	PRIMO 42D
Net Volume (liters)	29.3	35.4	42
Dimensions HxWxD (mm)	520 x 400 x 425	520 x 400 x 475	418 x 550 x 490
Watts (W)	65	85	65
Voltage (V)	220/240	220/240	220/240
Amps	0.56	0.60	0.56
Energy Consumption (kWh/24h)*	0.58	0.60	0.62
Net Weight (kgs)	15.5	16.5	18.5
Noise Level (dB)	0 dB	0 dB	0 dB
Certification	ISO 9001 2008 / ISO 14001 2004 / CE / ROHS / WEEE		

Ventilation requirements for built-in minibars: A channel for air circulation is imperative for ventilation and operation. A minimum open area of 200 cm² is required for proper ventilation. Please refer to the *Minibar Case Good Specifications Manual* for all details.

Specifications may change without notice due to continuous product development.

*Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.

**Add 23 mm to the depth of the PRIMO 42D for handle.



MINIBAR SYSTEMS

smart bars • smart people • smart solutions

A SWISS COMPANY

www.minibar.sg

DOC0183_PrimoCollection_Asia_Rev-2

UPDATED CATALOGUE

ANGLO-EAST TRADING CO. (HK) LTD
ROOM 906, BLOCK B, PO LUNG CENTRE, 11 WANG CHIU ROAD,
KOWLOON BAY, KOWLOON, HONG KONG

英東貿易(香港)有限公司
香港九龍九龍灣宏照道11號寶隆中心B座906室

TEL: (852) 2375 1111 FAX: (852) 2375 3409
E-MAIL: SALES@ANGLO-EAST.HK

CONTACT US